

GROUND BEAMS SCHEDULE

TYPE	SIZE		UPPER RFT.	STIRRUPS	REMARKS
	WIDTH	DEPTH			
GB1	300	600	4 Y 16	6R8/m	
GB2	300	700	6 Y 16	6R8/m	

FOOTINGS SCHEDULE (ISOLATED FOOTINGS)

FOOTING NUMBER	SIZE			REINFORCED CONCRETE FOOTING			REINFORCEMENT		REINFORCEMENT	
	LENGTH	WIDTH	DEPTH	LENGTH	WIDTH	DEPTH	BOTTOM REINFORCEMENT		TOP REINFORCEMENT	
							LONG DIRECTION	SHORT DIRECTION	LONG DIRECTION	SHORT DIRECTION
F0	1400	1400	200	1000	1000	600	8Y12/m'	8Y12/m'	8Y12/m'	8Y12/m'
F1	1700	1700	200	1300	1300	600	8Y12/m'	8Y12/m'	8Y12/m'	8Y12/m'
F2	2200	2400	200	1800	2000	600	8Y12/m'	8Y12/m'	8Y12/m'	8Y12/m'
F3	2400	2800	200	2000	2400	600	6Y16/m'	6Y16/m'	6Y16/m'	6Y16/m'
F4	2800	3200	200	2400	2800	600	8Y16/m'	8Y16/m'	8Y16/m'	8Y16/m'
F5	2900	3400	200	2500	3000	600	8Y16/m'	8Y16/m'	8Y16/m'	8Y16/m'
F6	3600	4100	200	3200	3700	600	8Y18/m'	8Y18/m'	8Y18/m'	8Y18/m'
F7	1600	4100	200	1200	3700	600	6Y16/m'	6Y12/m'	6Y16/m'	6Y12/m'
F8	2400	3700	200	2000	3300	600	6Y16/m'	6Y16/m'	6Y16/m'	6Y16/m'

